



VEEPEAK OBDCheck VP11 Mini Bluetooth OBD II Scanner Adapter Car Diagnostic Code Reader Scan Tool User Manual

[Home](#) » [VEEPEAK](#) » VEEPEAK OBDCheck VP11 Mini Bluetooth OBD II Scanner Adapter Car Diagnostic Code Reader Scan Tool User Manual 

Contents

- [1 VEEPEAK OBDCheck VP11 Mini Bluetooth OBD II Scanner Adapter Car Diagnostic Code Reader Scan Tool](#)
- [2 Product Specifications](#)
- [3 Setup Instructions](#)
- [4 FAQs and Troubleshooting](#)
- [5 Disclaimer](#)
- [6 FCC](#)
- [7 SCANNER](#)
- [8 Support and Warranty](#)
- [9 Documents / Resources](#)
 - [9.1 References](#)
- [10 Related Posts](#)



VEEPEAK OBDCheck VP11 Mini Bluetooth OBD II Scanner Adapter Car Diagnostic Code Reader Scan Tool



The Veepeak OBDCheck VP11 is an easy-to-use inexpensive and small OBD2 device that turns your Bluetooth-enabled Android or Windows smartphone or tablet into a sophisticated diagnostic scan tool and real-time parameter monitor. Read and clear trouble codes, reset Check Engine light as well as display live sensor readings with the use of a downloaded OBD2 App such as Torque. The adapter works on OBD II compliant vehicles and is a very useful little gadget that will save you time and money.

Note

- It's recommended that you unplug the device if it will not be used for some time (on cars with old batteries, the time should be shorter).
- Do not have any operations on the app while driving. Always focus on driving.
- Simply erasing the trouble code does not mean the fault has been solved. You should repair your vehicle as soon as possible.
- Not all trouble codes can be read as OBD2 is primarily designed for engine diagnostics systems. Other systems like ABS, SRS, VSC, TPMS etc. use different protocols to communicate so check the app capabilities.
Generally what you can do with the device depends on what features the app provides.

Compatible Vehicles (OBD-II or EOBD) (Cars and light trucks made since the following year):

- **US:** 1996,
- **Canada:** 1998,
- **Mexico:** 2006,
- **Australia:** 2006 (gas), 2007 (diesel)
- **Brazil:** 2007 (gas)
- **European Union & UK:** 2001 (gas), 2004 (diesel)

India: 2010

Mexico: 2006, etc.

Product Specifications

1. Communication method: Bluetooth
2. **Supported Devices:** Android phone & tablet, Windows phone, tablet & pc

3. **Operating voltage:** 9V~16V
4. **Operating current:** 25mA
5. **Working temperature:** -40~85°C
6. **Dimension:** 1.89 x 1.26 x 0.98 inches
7. **Supported OBD || Protocols:** SAE J1850 PWM, SAE J1850 VPW, ISO 9141-2, ISO14230-4 (KWP2000), and ISO15765-4 CAN

Setup Instructions

- **Step 1:** Download and install the APP at your choice onto your phone (see compatible app list in Part IV).
- **Step 2:** Plug the adapter into the OBD II port on your vehicle. Make sure it fits well. (Red LED On)
- **Step 3:** Turn the ignition key to the ON position (or start the engine). For Push Button Start vehicles, press the button once to twice without putting your foot on the brake pedal (check your car manual).
- **Step 4:** Enable Bluetooth on your phone and pair with "OBDII" (You may need to wait for a few seconds for "OBDII" to show up; PIN is 1234).
- **Step 5:** Run the APP, make any necessary connection settings, and connect.

Compatible Apps (may require separate purchase) and Settings

- **Android:** Torque Lite/Pro, OBD Fusion, DashCommand, Car Scanner ELM OBD2, OBD Auto Doctor, Dr Prius, Piston and other ELM327 compatible Apps
- **Windows:** OBD Auto Doctor, EOBD Facile, Car Scanner, etc.
- **Torque:** Setting > OBD2 Adapter Setting>
- **Connection Type:** Bluetooth; Choose Bluetooth
- **Device:** OBDII. Quit and restart Torque.
- **DashCommand:** Settings > OBD-II Interface
- **Type:** Select "ELM" Other Apps have similar settings. If you are not sure. contact us.

FAQs and Troubleshooting

1. Is an app required?

An OBD2 app is required to work with the adapter and the functions you can get mainly depend on the app you use. It requires a download from the Google Play Store and some may need separate purchases.

2. Does it work with iOS devices? Or Android head units?

Unfortunately, the VP11 does not work with iOS due to Apple's limitations. You should choose the Bluetooth LE (4.0) model for iOS. The Vp11 may have compatibility issue with some Android head units and we do not have a support list due to the complexity of the market.

3. Could not pair with "OBDII"

Turn off & on Bluetooth; restart your phone and try again. When OBDII shows as paired, connected, or previously connected, you can start the app to connect.

4. Can I leave the adapter plugged in all the time?

You can leave the adapter plugged in all the time if your car battery is not too old. If you leave your car sitting for more than 1 week, we recommend that you remove the adapter.

5. "OBDII" is not showing up on my phone's Bluetooth device list.

First, check if the red light is on. If not, check if the cigar fuse of your vehicle is in good condition. You can also try with another vehicle to verify.

6. App not connecting to OBD-II adapter.

Make sure the app is compatible, "OBDII" is paired with your phone and you have made the required App connection setting.

7. Cannot connect to vehicle/ECU.

Verify if your vehicle is OBD2 compliant. Make sure the ignition key is ON or start the vehicle to try. Then try it on another vehicle.

8. Can it reset my ABS, airbag, and other non-Check Engine lights?

Most OBD2 Apps only provide basic check engine light diagnostics. You will need a specific

An app that can do diagnostics on these modules on your specific vehicle. Contact us or the app developer if you are not sure. It cannot reset oil change or maintenance required lights.

9. Which sensor data can I get?

Readable parameters depend on what's installed on the OBDII system by the manufacturer. Generally, newer vehicles will give more readings and faster refresh speed. Some parameters like transmission temp are manufacturer-specific and you will need to add a custom PID.

10. The adapter does not fit into the recessed area of the OBD port or is hard to plug in and out.

Use our OBD2 extension cable (search for Veepeak OBD2 extension cable on Amazon)

If you cannot find the answer or have trouble getting the device to work, please feel free to reach out to us for assistance.

Disclaimer

Features and functions are offered and achieved through third-party Apps. Product names, logos, brands, vehicle makes/models, and other trademarks featured or referred to within this user manual are the property of their respective trademark holders. Use of them does not imply any affiliation with or endorsement of them.

Scan the QR code or visit www.veepeak.com to get the latest FAQ & troubleshooting, user manual and customer support.



FCC

ISED Canada Statement

This device contains license-exempt transmitters/receivers that comply with Innovation, Science, and Economic Development Canada's license-exempt RSS(s).

Operation is subject to the following two conditions:

1. this device may not cause interference.
2. this device must accept any interference, including interference that may cause undesired operation of the

device.

RF Exposure Statement

This equipment complies with Canadian radiation exposure limits set forth for an uncontrolled environment. To maintain compliance with IC’s RF Exposure guidelines, this equipment should be installed and operated with a minimum distance of 20cm between the radiator and your body. This device and its antenna(s) must not be co-located or operated in conjunction with any other antenna or transmitter.

SCANNER

Scan the QR code or visit www.veepeak.com to get the latest FAQ & troubleshooting, user manual, and customer support.



Support and Warranty


For technical support or warranty service, please contact us via one of the following ways:

- Phone: +1 (833) 303-1434, 9:00 AM – 5:00 PM CST, Monday – Friday
- Email: support@veepeak.com
- Visit www.veepeak.com to submit a contact form.

Please describe your issue in as many details as possible and include a screenshot if you get any error messages. Emails usually be answered within 24 hours.

Products are covered by a one-year hassle-free replacement warranty against defects.

Documents / Resources

	VEEPEAK OBDCheck VP11 Mini Bluetooth OBD II Scanner Adapter Car Diagnostic Code Reader Scan Tool [pdf] User Manual OBDCheck VP11 Mini Bluetooth OBD II Scanner Adapter Car Diagnostic Code Reader Scan Tool, OBDCheck VP11, Mini Bluetooth OBD II Scanner Adapter Car Diagnostic Code Reader Scan Tool, Adapter Car Diagnostic Code Reader Scan Tool, Diagnostic Code Reader Scan Tool, Reader Scan Tool
---	---

References

- [User Manual](#)

