

VELOGK VL-CC20 Retractable Car Charger User Manual

Home » VELOGK » VELOGK VL-CC20 Retractable Car Charger User Manual

Contents

- 1 VELOGK VL-CC20 Retractable Car
- Charger
- **2 Product Features**
- **3 Product Parameters**
- **4 Usage Instructions**
- **5 Safety Precautions**
- **6 WARRANTY CLAIM TERMS &**

CONDITIONS

- 7 Documents / Resources
 - 7.1 References



VELOGK VL-CC20 Retractable Car Charger



Product Features

Quick Charging Capability

- The Retractable Car Charger ensures efficient and consistent charging for your devices.
- It comes equipped with overcharge, overcurrent, overvoltage, temperature control, and short-circuit protection to safeguard your device's battery from overcharge damage.

Flexible Retractable Design

The Retractable Car Charger features a retractable design, allowing you to extend the charging cable within an 80cm range. When not in use, it automatically retracts, keeping your setup tidy and free from tangled cables. It's designed for convenient control and usage.

Multi-Fast Charging Protocol Certification

This car charger is compatible with devices supporting various fast charging protocols, including PD, QC3.0, AFC, MTK, and FCP. It's suitable for a wide range of devices, including iPhones (14/13/12/11/Plus/Pro/Pro Max/mini/XS/XS Max/XR/X/8 Plus/8/7 Plus/7/6S/6), Samsung Galaxy series (Note 20 Ultra/Note10 Plus/S23/S22/S22+/S22 Ultra/S21+/S20/S10 5G/A54/S/S9 Plus/S8+/Note 9), Google Pixel series (Pixel 7/7a/6/6a/5/4xl/3xl/2xl/3a/4/4a/Nexus 6P), and more.

Suitable for Various Vehicle Models

The Car Charger is compatible with a wide range of vehicle models. It fits securely into the standard 12V-24V car sockets and won't pop out even when driving on bumpy roads.

Product Parameters

• Product Dimensions: 139 x 65 x 34.5mm

• Product Material: ABS+PC+Aluminum Alloy

• Product Power: Up to 60W

• Extended Cable Length: 800mm

• Input Voltage: 12V-24V

• Lightning Connector Output: 5V/2.4A Type-C

Connector Output: 9V/2A
USB-A Port Output: 5V/2.4A
Type-C Port Output: 5V/3A

Usage Instructions



- 1. Insert the Retractable Car Charger into your vehicle's car cigarette lighter socket.
- 2. Extend the charging cable and connect it to your device.
- 3. Start your vehicle's ignition, and the Retractable Car Charger will begin charging your device.

Retraction Guidelines: Hold onto the cable, give it a gentle 1cm extension, and then release; the cable will retract automatically.

Safety Precautions

- 1. Ensure proper connection of the Retractable Car Charger and avoid using damaged charging cables.
- 2. Keep the Retractable Car Charger away from damp or high-temperature environments.
- 3. In case of any unusual occurrences, cease using the Retractable Car Charger immediately and contact our customer service.

WARRANTY CLAIM TERMS & CONDITIONS

- We offer a 360-day hassle-free replacement or refund policy for the Retractable Car Charger.
- If you encounter any quality issues while using the product, we are ready to provide replacements or refunds.
- Our customer service support is available 24/7 and for the lifetime of the product.

Have issues with your product?

Things go wrong sometimes. But you can easily have our friendly team troubleshoot and fix the issues for you kegaftersales@gmail.com

Documents / Resources



<u>VELOGK VL-CC20 Retractable Car Charger</u> [pdf] User Manual VL-CC20 Retractable Car Charger, VL-CC20, Retractable Car Charger, Charger

References

• User Manual

Manuals+, Privacy Policy

This website is an independent publication and is neither affiliated with nor endorsed by any of the trademark owners. The "Bluetooth®" word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. The "Wi-Fi®" word mark and logos are registered trademarks owned by the Wi-Fi Alliance. Any use of these marks on this website does not imply any affiliation with or endorsement.