WELVAN-SW2

HDMI 2.0 2x1 Switcher with HDR & CEC





All Rights Reserved

Version: WUH2-H2_2018V1.0

WELVAN 2×1 Switcher with HDR & amp; CEC User Manual

Home » WELVAN » WELVAN 2×1 Switcher with HDR & amp; CEC User Manual

2x1 Switcher with HDR & CEC

WELVAN-SW2

HDMI 2.0 2x1 Switcher with HDR & CEC





All Rights Reserved

Version: WUH2-H2_2018V1.0

Contents

- 1 Preface
- **2 FCC Statement**
- **3 SAFETY PRECAUTIONS**
- 4 1. Product Introduction
 - **4.1 1.1 Features**
 - 4.2 1.2 Packing List
- 5 2. Specification
- 6 3. Panel Description
 - 6.1 3.1 Front Panel
 - 6.2 3.2 Rear Panel
- 7 4. System Connection
 - 7.1 4.2 System Diagram
- 8 5. Panel Drawing
- 9 6. Troubleshooting &

Maintenance

- 10 7. Customer Service
- 11 Documents / Resources
- **12 Related Posts**

Read this user manual carefully before using the product. Pictures shown in this manual are for reference only. Different models and specifications are subject to real products.

This manual is only for operation instruction, please contact the local distributor for maintenance assistance. The functions described in this version were updated till April 2018. In the constant effort to improve the product, we reserve the right to make functions or parameter changes without notice or obligation. Please refer to the dealers for the latest details.

FCC Statement

This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. It has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a commercial installation. Operation of this equipment in a residential area is likely to cause interference, in which case the user at their own expense will be required to take whatever measures may be necessary to correct the interference. Any changes or modifications not expressly approved by the manufacture would void the user's authority to operate the equipment.







SAFETY PRECAUTIONS

To ensure the best performance from the product, please read all instructions carefully before using the device. Save this manual for further reference.

- Unpack the equipment carefully and save the original box and packing material for possible future shipment.
- Follow basic safety precautions to reduce the risk of fire, electrical shock, and injury to persons.
- Do not dismantle the housing or modify the module. It may result in electrical shock or burn.
- Using supplies or parts not meeting the products' specifications may cause damage, deterioration, or malfunction.
- Refer all servicing to qualified service personnel.
- To prevent fire or shock hazards, do not expose the unit to rain, moisture or install this product near water.
- Do not put any heavy items on the extension cable in case of extrusion.
- Do not remove the housing of the device as opening or removing housing may expose you to dangerous voltage or other hazards.
- Install the device in a place with fine ventilation to avoid damage caused by overheat.
- Keep the module away from liquids.
- Spillage into the housing may result in fire, electrical shock, or equipment damage. If an object or liquid falls or spills onto the housing, unplug the module immediately.
- Do not twist or pull by force ends of the optical cable. It can cause malfunction.
- Do not use liquid or aerosol cleaners to clean this unit. Always unplug the power to the device before cleaning.
- Unplug the power cord when left unused for a long period of time.
- Information on disposal for scrapped devices: do not burn or mix with general household waste, please treat them as normal electrical wastes.

1. Product Introduction

The WUH2-H2 is an ultra-thin HDMI 2.0 Switcher with two HDMI video inputs and one HDMI output. The switcher supports HDMI video resolution up to 4K@60Hz 4:4:4. The SOURCE switch on the front panel is designed to switch any one of the inputs to output. Moreover, the switcher supports CEC and HDR. No need for any external power supply, simplifying the installation and operation.

1.1 Features

- Supports HDMI 2.0 4k@60Hz 4:4:4.
- · HDCP2.2 compliant
- · Supports HDR.
- Supports CEC pass-through.
- No need for an external power supply.

1.2 Packing List

- 1x HDMI 2.0 2×1 Switcher
- 1x Velcro Tape
- 1x User Manual


Note: Please contact your distributor immediately if any damage or defect in the components is found.

2. Specification

Video Input		
Input	(2) HDMI	
Input Connector	(2) Female type-A HDMI	
HDMI Input Resolution	Up to 4Kx2K@60Hz 4:4:4	
HDMI Standard	2.0	
HDCP Version	2.2	
Video Output		
Output	(1) HDMI	
Output Connector	(1) Female type-A HDMI	
HDMI Output Resolution	Up to 4Kx2K@60Hz 4:4:4	
HDMI Standard	2.0	
HDCP Version	2.2	
General		
Bandwidth	18Gbps	
HDMI Cable Length	From source to display device:	
	1080P@60Hz 4:4:4 ≤ 10m, 4K@60Hz 4:4:4 ≤ 4.5m	
Operation Temperature	-5 ~ +55°C	
Storage Temperature	-25 ~ +70℃	
Relative Humility	10%-90%	
Max Power Consumption	90mW	
Dimension (W*H*D)	86mm x 16mm x 55mm	
Net Weight	135g	


3. Panel Description

3.1 Front Panel



- 1. SOURCE: Press the button to switch to the next input.
- 2. HDMI OUT: Type-A female HDMI output port to connect HDMI display.
- 3. INPUT LED: The LED illuminates blue when there is HDMI input on the corresponding channel.

3.2 Rear Panel



1 HDMI IN 1~2: Two Type-A female HDMI input ports to connect HDMI sources.


4. System Connection

4.1 Usage Precautions


- Make sure all components and accessories included before installation.
- The system should be installed in a clean environment with proper temperature and humidity.
- All of the power switches, plugs, sockets, and power cords should be insulated and safe.
- All devices should be connected before power on.

4.2 System Diagram

The following diagram illustrates typical input and output connection that can be utilized with the switcher:



5. Panel Drawing



6. Troubleshooting & Maintenance

Problems	Potential Causes	Solutions
Colour losing or no video signal output in HDMI display.	The connecting cables may not be connected correctly or it may be broken.	Check whether the cables are connected correctly and in working condition.
	The display is not compatible with the present output resolution.	Make sure the resolution of the display(s) is compatible with the present resolution.
No HDMI signal output in the splitter while local HDMI input is in normal working state.	The connecting cables may not be connected correctly or it may be broken.	Check whether the cables are connected correctly and in working condition.
Splash screen in output devices.	Poor quality of the connecting cable.	Change for another cable of good quality.

Note: If your problem still remaining after following the above troubleshooting steps, please contact your local dealer or distributor for further assistance.

7. Customer Service

The return of a product to our Customer Service implies the full agreement of the terms and conditions hereinafter. These terms and conditions may be changed without prior notice.

1) Warranty

The limited warranty period of the product is fixed for three years.

2) Scope

These terms and conditions of Customer Service apply to the customer service provided for the products or any other items sold by authorized distributors only.

3) Warranty Exclusions:

- · Warranty expiration.
- The factory-applied serial number has been altered or removed from the product.
- Damage, deterioration, or malfunction caused by:
 - Normal wear and tear.
 - Use of supplies or parts not meeting our specifications.
 - No certificate or invoice as proof of warranty.
 - The product model showed on the warranty card does not match with the model of the product for repairing or had been altered.
 - Damage caused by force majeure.
 - · Servicing not authorized by the distributor.
 - Any other causes which do not relate to a product defect.
- Shipping fees, installation, or labor charges for installation or setup of the product.
- **4) Documentation:** Customer Service will accept defective product(s) in the scope of warranty coverage at the sole condition that the defeat has been clearly defined, and upon reception of the documents or copy of the invoice, indicating the date of purchase, the type of product, the serial number, and the name of the distributor. **Remarks:** For further assistance or solutions, please contact your local distributor.

Documents / Resources



WELVAN 2x1 Switcher with HDR & CEC [pdf] User Manual 2x1 Switcher with HDR CEC, HDMI 2.0, SW2

Manuals+,