

## WOLFVISION Pro Solution Link



# WOLFVISION Pro Solution Link Installation Guide

[Home](#) » [WOLFVISION](#) » WOLFVISION Pro Solution Link Installation Guide 

## Contents

- 1 WOLFVISION Pro Solution Link
- 2 Product Information
- 3 About this Guide And Copyright
- 4 System Requirements
- 5 On-Premise or Management Hub
- 6 Server Installation
- 7 Installing .NET Core Windows Server Hosting
- 8 Start the application
- 9 Updating vSolution Link Pro
- 10 Move from Desktop Installation to IIS Installation
- 11 Index
- 12 Contact
- 13 Documents / Resources
  - 13.1 References



WOLFVISION Pro Solution Link



## Product Information

### Specifications

- **Brand:** WolfVision GmbH
- **Product:** vSolution Link Pro
- **System Requirements:** Windows Web Services (IIS Internet Information Server)

### Frequently Asked Questions

- **Q:** Can vSolution Link Pro be accessed from any device in the local network?
  - **A:** Yes, as long as the device has a modern fully HTML5 compatible browser.
- **Q:** What are the essential requirements for using vSolution Link Pro?
  - **A:** You need to install it on a Windows IIS server, configure email credentials, SSL certificate, ensure internet access, and maintain 24/7 server availability.

## About this Guide And Copyright

### About this Guide

This document explains the setup of vSolution Link Pro application by WolfVision on a Windows IIS server.

### Copyright

The software is the property of WolfVision and its licensors. Any reproduction in whole or in part is strictly prohibited. No part of this document may be copied, reproduced, or transmitted by any means, without prior written permission from WolfVision except documentation kept by the purchaser for backup-purposes.

In the interest of continuing product improvement, WolfVision reserves the right to change product specifications without notice.

Information in this document may change without prior notice.

**Disclaimer:** WolfVision shall not be liable for technical or editorial errors or omissions.  
Use of Trademarks, Registered Trademarks, and other Protected Names and Symbols

This manual may make reference to trademarks, registered trademarks, and other protected names and/or symbols of third-party companies not related in any way to WolfVision. Where they occur these references are for illustrative purposes only and do not represent an endorsement of a product or service by WolfVision, or an endorsement of the product(s) to which this manual applies by the third-party company in question. Regardless of any direct acknowledgement elsewhere in the body of this document, WolfVision hereby acknowledges that all trademarks, registered trademarks, service marks, and other protected names and/or symbols contained in this manual and related documents are the property of their respective holders.

2023-10-27

## System Requirements

### Windows Web Services (IIS Internet Information Server)

- As vSolution Link Pro is a web server application, it can be accessed by any modern fully HTML5 compatible browser of a third-party device in the local network.
- To use all features the application provides, it has to be installed as IIS (Internet Information Server). Email credentials, SSL certificate, Internet access and 24/7 server availability are also required.

**The software (64bit application) can be installed on following operating systems. The following shows the minimum system requirements, more recommended:**

- Windows Server 2019 or newer (all requirements according to Microsoft must be fulfilled)
- CPU minimum 1 Core with 2.60GHz (2 cores, or more recommended)
- 4GB RAM (8GB, or more recommended)
- 100GB minimum free disk space for firmware files (250GB, or more recommended)
- Access to secure port (e.g. 443, https default)
- Server address (IP:port) has to be reachable via secure web socket (wss)
- NET Core Hosting Bundle, tested with version 7.0.3

### Please note

Latest updates recommended.

Earlier versions of operating systems are not tested and may not be supported.

Please note the required disk space for the local firmware repository, disk space of at least 20GB is

recommended.

To access the devices, they have to be online and in the same network to be reachable! Pay attention of correct network settings, especially when running in special network environments.

Cynap systems will disable their LAN ports when powering down by default and can be powered up by using the Wake on LAN functionality. For network infrastructures with blocked Wake on LAN, use power down mode Power Save to keep the LAN port of your Cynap active. When using WolfVision Visualizer devices, use power down modes Normal or ECO to keep the LAN port active. Certain Visualizer models are supporting Wake on LAN (check power down mode of connected Visualizer).

An incorrect system time may cause network connection to fail, the use of a valid timeserver is recommended.

## **Custom Email-Provider**

Valid custom email-provider credentials are required when enabling:

- 2-factor authentication
- Management Hub
- Event log Email notification
- Box Replacement\*
- Password reset\*.

\* If no custom provider is set, the integrated Sendgrid account will be used for sending Emails.

## **SSL certificate – prerequisite for enabling Management Hub**

A valid SSL certificate is required when restricting the access to https.

## **Firewall Rules**

Ensure that all necessary ports, services and IP addresses are available and not blocked by your firewall (external and personal). Acknowledgements (“ACKs”) of TCP packets are not considered in the following table in order to be able to illustrate the direction of the data packets. Since acknowledgements are usually sent back via the same TCP port, the other direction shall not be blocked to ensure smooth functioning.

On certain systems, you have to set a rule to allow the application: WolfVision.MgmtTool.Api.exe for full functionality.

Function / Application	Port	Type	Inbound / Outbound	Description
<b>vSolution Link Pro</b>				
Wake On LAN	7 / 9	UDP	Inbound / Outbound	Wake On LAN – Usually port 7 is used for sending the magic packet
DNS	53	TCP / UDP	Inbound / Outbound	DNS – This port will be used for Domain Name System. If this port is blocked, DNS service are not available
http, Cynap control	80	TCP	Inbound / Outbound	This is the default port to connect to the web interface (httpd) of vSolution Link Pro. If this port is blocked, connection cannot be established
https, SSL, e.g. Cloud Service, Cynap control	443	TCP	Inbound / Outbound	This is the default port to connect to web interface (https) of vSolution Link Pro. If this port is blocked, connection cannot be established.
SMTP	587	SMTP	Outbound	Mail Server – Port for communication with SMTP server.
Discovery Multicast	50000	UDP	Inbound	This port is used for device discovery of all available Cynap and Visualizer in the network by vSolution applications (uses Multicast IP address 239.255.255.250). If this port is blocked, device discovery is not possible
Device Discovery	50913	UDP	Inbound	This port is used for device discovery. If this port is blocked, device discovery is not possible.
For control purposes	50915	TCP	Inbound / Outbound	This port is used for control purposes. If this port is blocked, no control is possible


## On-Premise or Management Hub

The vSolution Link Pro is a web server application and needs to be installed, preferably on a server to ensure 24/7 availability.

### Hosted On-Premise (Local Installation)

- When the application is hosted on-premise, this server, all Cynap and Visualizer systems and also the third party devices (desktops, workstations, tablets) have to be in the same Ethernet network.

### Hosted with Management Hub (Cloud Installation)



- When the application is hosted with enabled Management Hub feature, Cloud supported devices can be managed additionally.

### Supported WolfVision Cynap systems in Management Hub:

- Cynap
- Cynap Pro
- Cynap Core
- Cynap Core Pro
- Cynap Pure
- Cynap Pure Pro
- Cynap Pure Receiver
- Cynap Pure SDM

For full compatibility, keep installed firmware version of all your devices up to date.

## Server Installation

### Server Installation (Windows IIS)

The vSolution Link Pro is a web server application and needs to be installed, preferred on a server to ensure 24/7 availability.

Different versions of IIS may vary slightly, the following steps are describing the installation on a Windows Server 2019 Datacenter (OS build 17763.1131) with .NET Core Hosting Bundle version 7.0.3. The installation on other versions may vary. vSolution Link Pro is delivered with a standard web.config, which can be adopted, depending on your needs.


Note additional settings for using Management Hub (cloud access) feature.

### Download the installation files

- Download the zip archive vSolutionLinkPro\_WindowsServer.zip from the WolfVision web page and unpack it.


### Add IIS functionality

Open the Server Manager Dashboard and Add Roles and Features:



## Important

- WebDAV role should stay disabled for vSolution Link Pro server for full functionality.



Add Roles and Features Wizard

Select installation type

DESTINATION SERVER  
wviis01.wolfvision-at.intra

Before You Begin

Installation Type

Server Selection

Server Roles

Features

Confirmation

Results

Select the installation type. You can install roles and features on a running physical computer or virtual machine, or on an offline virtual hard disk (VHD).

☒ **Role-based or feature-based installation**  
Configure a single server by adding roles, role services, and features.

☐ **Remote Desktop Services installation**  
Install required role services for Virtual Desktop Infrastructure (VDI) to create a virtual machine-based or session-based desktop deployment.



< Previous

Next >

Install

Cancel





## Add features that are required for Web Server (IIS)?


The following tools are required to manage this feature, but do not have to be installed on the same server.



- ▾ Web Server (IIS)
  - ▾ Management Tools
    - [Tools] IIS Management Console

☒ Include management tools (if applicable)

Add Features

Cancel





#### 1. 5.4. Select WebSocket Protocol (Application Development, sub item of IIS Web Server)

Add Roles and Features Wizard

Select role services

DESTINATION SERVER  
wvlis01.wolfvision.at:Intra

Before You Begin

Installation Type

Server Selection

Server Roles

Features

Web Server Role (IIS)

**Role Services**

Confirmation

Results

Select the role services to install for Web Server (IIS)

Role services

☐ Windows Authentication

☒ Application Development

☐ .NET Extensibility 3.5

☐ .NET Extensibility 4.7

☐ Application Initialization

☐ ASP

☐ ASP.NET 3.5

☐ ASP.NET 4.7

☐ CGI

☐ ISAPI Extensions

☐ ISAPI Filters

☐ Server Side Includes

☒ WebSockets Protocol

☐ FTP Server

☐ FTP Service

☐ FTP Extensibility

☒ Management Tools

☒ IIS Management Console

☐ IIS 6 Management Compatibility

Description

IIS 10.0 and ASP.NET 4.7 support writing server applications that communicate over the WebSockets Protocol.

< Previous

Next >

Install

Cancel

Add Roles and Features Wizard

Confirm installation selections

DESTINATION SERVER  
wvlis01.wolfvision.at:Intra

Before You Begin

Installation Type

Server Selection

Server Roles

Features

Web Server Role (IIS)

Role Services

**Confirmation**

Results

To install the following roles, role services, or features on selected server, click Install.

☐ Restart the destination server automatically if required

Optional features (such as administration tools) might be displayed on this page because they have been selected automatically. If you do not want to install these optional features, click Previous to clear their check boxes.

Web Server (IIS)

Management Tools

IIS Management Console

Web Server

Application Development

WebSockets Protocol

Common HTTP Features

Default Document

Directory Browsing

HTTP Errors

Static Content

Export configuration settings



Specify an alternate source path

< Previous


Next >

Install


Cancel




**Prepare file structure**




- Copy the unzipped folder vSolutionLinkPro\_WindowsServer to c:\inetpub\wwwroot






- Change properties to manage permissions of the IIS to allow full control

## Start Internet Information Services (IIS) Manager




## Setup IIS

- Manage sites of IIS and add the physical path




- Restrict access to https and check the used port.
- This setting is required prior activating Management Hub feature.




- Define your valid SSL certificate for proper https connection.
- This setting is required prior activating Management Hub feature.







- Change .NET CLR version in Basic Settings to “No Managed Code”
- Change Managed pipeline mode to “Integrated”.



- Change Start Mode in Advanced settings to “AlwaysRunning” to allow 24/7 operation



- Change Idle Time-out (minutes) in Advanced settings to “0”



## Please note

When the IIS is running OnDemand, it stops when:

- No vSolution Link Pro window is open in a browser window at any client
- No Management Hub connection is open
- No device uses calling home.

## Installing .NET Core Windows Server Hosting

Install the .NET Core Hosting Bundle.

The application was tested with .NET version 7.0.3:

- <https://dotnet.microsoft.com/en-us/download/dotnet/thank-you/runtime-aspnetcore-7.0.3-windows-hosting-bundle-installer>

For further details about IIS, please visit:

- <https://docs.microsoft.com/en-us/aspnet/core/host-and-deploy/iis/?view=aspnetcore-7.0>

Stop and restart the service at Application Pool Tasks at IIS Manager.

### Adopt appsettings.json

- The file appsettings.json allows modifying all settings offline by using a common text editor.
- The most important settings are accessible at the graphical user interface (Configuration – Settings).

### Using Management Hub (Cloud)




```
appsettings.json - Notepad
File Edit Format View Help
{
  "Hosting": {
    "AppName": "vSolution Link Pro",
    "Port": 80,
    "HttpsPort": 443,
    "UseHttps": true,
    "CertificatePath": "C:\\ProgramData\\WolfVision\\vSolution Link Pro\\certificate.pfx",
    "CertificateKey": "Dvx_pGpc4z2e_F4m_Dp@",
    "EnableSwagger": false,
    "Enable2FA": false,
    "MaxRequestBodySize": null
  },
  "MailServer": {
    "ProviderType": 0,
    "MailServer": "",
    "MailPort": 587,
    "Sender": "",
    "Username": "",
    "Password": "P@ssw0rd",
    "UseAuthentication": false,
    "ConnectionSecurity": 1,
  }
}
```

- “UseHttps” in section “Hosting” has to be set to “true”.

### Activate Management Hub (optional, depending on setup)

The Management Hub for Cloud support needs to be enabled in the setting at initial start:



**Alternative, activate the Management Hub in the file appsettings.json and adopt all settings according your needs manually:**


```

appsettings - Notepad
File Edit Format View Help
{
  "DeviceManagement": {
    "UseMock": false,
    "StatusConnectedThreshold": 45,
    "AllowedSecondsForRestart": 180,
    "DeviceDiscoveryEnabled": true,
    "PollCycleSeconds": 15,
    "CommunicationTimeout": 5000,
    "WakeOnLanPort": 9,
    "WakeOnLanWaitSeconds": 60,
    "WakeOnLanActive": false,
    "UnassignedDevicesVisible": false,
    "DiscoveryTimeout": 1000,
    "DownloadWebUiTimeout": 60,
    "ManagementHub": {
      "Enabled": true,
      "KeepAliveTimeout": 5,
      "EmailNotification": {
        "Enabled": true,
        "HostingDomain": "https://my_vsolutionlinkpro.com",
        "Interval": "*/*/*/*/*",
        "Receivers": [
          "armin@wolf.net"
        ]
      },
      "IsActive": true
    }
  }
}
Ln 21, Col 73 100% Windows (CRLF) UTF-8 with BOM

```

## Start the application

- To start vSolution Link Pro, open the browser of the workstation and enter the IP address of the server.
- Example URL <http://192.168.0.1:80>




- For security reasons, the default password has to be changed at first login.
- Please note, after inactivity of 30 minutes, you will be logged out automatically.

## Device Requirements

- To access the devices, they have to be online and reachable!
- Cloud-connected devices (Management Hub) are keeping a secure websocket connection (WSS) open to allow managing.
- E.g. Cynap devices will disable their LAN ports when powering down by default and can be powered up by using the Wake on LAN functionality. For network infrastructures with blocked
- Wake on LAN, use power down mode Power Save to keep the LAN port of your Cynap system active.
- Depending on network infrastructure and due to multiple network ports, IP routing has to be specified to route the network traffic.
- When using WolfVision Visualizer devices, use power down modes Normal or ECO to keep the LAN port active.

## First Login – Change Password (“admin” at initial start)

When you login the first time, the password must be set:



- When the blank Windows server IIS page should be opened, check the used ports and restart the server.

## Updating vSolution Link Pro

- Stop vSolution Link Pro at IIS Manager.
- Backup the `Data` folder from your current installation folder.
- Unpack the zip archive of the new version and copy the full content to the installation folder.
- Copy the content from your previously saved content of `Data` to the current `Data` folder.

## Important

- When the installation folder “vSolutionLinkPro” was exchanged, the permission has to be renewed (see chapter 5.5 Prepare file structure).


## Complete the update

- Start the vSolution Link Pro at the IIS Manager.


## Updating from version v1.8.0 (or earlier)

- When vSolution Link Pro version 1.8.0, or earlier was installed previously, the application pool has to be modified.


## Set Enable 32-Bit Applications to “False”



## Change Start Mode in Advanced settings to “AlwaysRunning” to allow 24/7 operation



## Change Idle Time-out (minutes) in Advanced settings to “0”



## Please note


When the IIS is running OnDemand, it stops when:

- No vSolution Link Pro window is open in a browser window at any client
- No Management Hub connection is open

- No device uses calling home.

## Check the settings files web.config and appsettings.json

- Verify web.config (will be found in the root folder of the IIS), hostingmodel has to
- Set Enable 32-Bit Applications to “False”



- Verify web.config (will be found in the root folder of the IIS), hostingmodel has to be set to “inprocess”.



- The setting “InProcessHostingModel” in the file appsettings.json is obsolete since Solution Link Pro v1.9 and later.
- This setting is ignored and has no effect anymore.





```
appsettings.json - Notepad
File Edit Format View Help
{
  "Hosting": {
    "AppName": "vSolution Link Pro",
    "Port": 80,
    "HttpsPort": 443,
    "UseHttps": true,
    "CertificatePath": "C:\\ProgramData\\WolfVision\\vSolution Link Pro\\certificate.pfx",
    "InProcessHostingModel": true,
    "CertificateKey": "Dvx_pGpc4z2e_F4m_Dp@",
    "EnableSwagger": false,
    "Enable2FA": false,
    "MaxRequestBodySize": null
  },
  "MailServer": {
    "ProviderType": 0,
    "MailServer": "",
    "MailPort": 587,
    "Sender": "",
    "Username": "",
    "Password": "P@ssw0rd",
    "UseAuthentication": false,
    "ConnectionSecurity": 1,
  }
}
```

## Move from Desktop Installation to IIS Installation

To move all data from a former desktop installation to a server installation, ensure that vSolution Link Pro is properly installed on the IIS server.

### Important

A fresh installation of vSolution Link Pro on the server with identical version number than the former desktop installation is strongly recommended.

By continuing with the following steps, all the data of the vSolution Link Pro installation on the server get lost.

1. Stop the vSolution Link Pro server at the IIS Manager.
2. Delete all files and subfolders of the `Data` folder on your IIS installation.
3. Default path:
  - C:\inetpub\wwwroot\vSolutionLinkPro\
4. Copy the entire contents of the `Data` folder from your desktop installation.

Default path:

- Windows desktop installation (hidden folder) C:\ProgramData\WolfVision\vSolution Link Pro\
  - MacOS desktop installation /Library/Application Support/WolfVision/vSolution Link Pro/
5. Paste the files into the `Data` folder of your IIS installation.
  6. Default path:
    - C:\inetpub\wwwroot\vSolutionLinkPro\

### Important

- Check all listed paths in the appsettings.json file and correct it accordingly.
- Default path on IIS: C:\\inetpub\\wwwroot\\vSolutionLinkPro\\Data\\Start the vSolution Link Pro at the IIS Manager.
- All settings and data of the former Desktop installation are transferred to the server, including login credentials.

## Index

Version	Date	Changes
1.9.1	2023-10-27	Update to vSolution Link Pro version 1.9.1 Added section "Move from Desktop Installation to IIS Installation".
1.9.0	2023-07-25	Update to vSolution Link Pro version 1.9.0 Added rules for updating the application.
The version numbering has been adapted to the versioning of the application.		
1.5	2023-05-17	Added Management Hub activation (Cloud)
1.4	2023-04-25	Update to vSolution Link Pro version 1.8.0
1.3	2022-06-21	.NET Core Update to version 5.0.17
1.2	2022-05-23	Added WebDAV note
1.1	2021-07-07	Updated Firewall rules
1.0	2021-03-09	Created

## Contact

### WolfVision GmbH



- Oberes Ried 14 A-6833 Klaus / AUSTRIA
- **Tel.** +43-5523-52250
- **Fax** +43-5523-52249
- **E-Mail:** [wolfvision@wolfvision.com](mailto:wolfvision@wolfvision.com)
- [www.wolfvision.com](http://www.wolfvision.com)

## Documents / Resources

	<p><b><a href="#">WOLFVISION Pro Solution Link</a></b> [pdf] Installation Guide Pro Solution Link, Solution Link, Link</p>
---	--

## References

-  [Presentation, Collaboration & Visualizer Systems - WolfVision GmbH](#)

-  [Host ASP.NET Core on Windows with IIS | Microsoft Learn](#)
-  [Download ASP.NET Core 7.0 Runtime \(v7.0.3\) - Windows Hosting Bundle Installer](#)
- [User Manual](#)

[Manuals+](#), [Privacy Policy](#)

This website is an independent publication and is neither affiliated with nor endorsed by any of the trademark owners. The "Bluetooth®" word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. The "Wi-Fi®" word mark and logos are registered trademarks owned by the Wi-Fi Alliance. Any use of these marks on this website does not imply any affiliation with or endorsement.