



D950 XS Power Deep Cycle 12-Volt Battery Owner's Manual

[Home](#) » [XS Power](#) » D950 XS Power Deep Cycle 12-Volt Battery Owner's Manual 



12V/14V/16V
AGM POWER CELLS
SEALED NON-SPILLABLE LEAD ACID
BATTERIES AND ACCESSORIES
PN: 39-0071

Contents

- [1 REAL POWER UNREAL PERFORMANCE](#)
- [2 WARRANTY 3-YR](#)
- [3 Documents / Resources](#)
 - [3.1 References](#)
- [4 Related Posts](#)


REAL POWER UNREAL PERFORMANCE

Check Out Our Entire Line of XS Power Mobile Audio Products at XSPOWERBATTERIES.COM


MAX Amps Explained: CA and CCA have been used since 1914 as a definition for battery performance. CA is defined as a measurement of the number of amps a 12V battery can deliver for 30 seconds at 32 degrees F and not drop below 7.2 volts. CCA is the same test at 0 degrees F. These tests were designed for the cars of yesteryear that had to be cranked for a long time to get started. Back then, CA and CCA numbers were very meaningful. However for mobile audio use, immediate burst output is more important. XS Power batteries when compared to the batteries of yesteryear deliver much more of their power quickly. This instant burst of energy we

call “max amps”.




D375/ 12V AGM
12 Volt High Performance ACM Power Cell
MAX AMP : 800
CA: 300A **RC**: 25min **Ah**: 17
L: 7.87"(20mm)
W: 3.03-(77mm)
Weight: 11.5lbs (5.2kg)
600Watts 




D545/ 12V AGM
12 Volt High Performance AGM Power Cell
MAX AMP : 800
CA : 276A **RC**: 22min **Ah**: 17
L: 6.97" (177 m)
W: 3.38" (85mm)
H: 5.14"(131 mm)
Weight: 11.24 lbs (5.1kg)
600 Watts 



D680/ 12V AGM
12 Volt High Performance AGM Power Cell
MAX AMP : 1000
CA : 370A **RC**: 24min **Ah**: 20
L: 7.13" (181 m)
W: 3.03" (77 mm)
H: 6.57"(167 mm)
Weight: 13.51 lbs (6.2 kg)
1000 Watts 



<p>D950/ 12V AGM 12 Volt High Performance AGM Power Cell MAX AMP : 2100 CA : 605A RC: 58min Ah: 40 L: 9.8" (249 mm) W: 3.8" (97 mm) H: 5.77"(147 mm) Weight: 26.43 lbs (12 kg) 2000 Watts </p>	<p>D975/ 12V AGM 12 Volt High Performance AGM Power Cell MAX AMP : 2100 CA : 604A RC: 72min Ah: 43 L: 7.83" (199 mm) W: 5.3" (135 mm) H: 6.68"(170 mm) Weight: 28.5 lbs (12.95 kg) 2000 Watts </p>	<p>D1200/ 12V AGM 12 Volt High Performance AGM Power Cell MAX AMP : 2600 CA : 740A RC: 95min Ah: 55 L: 7.79" (198 mm) W: 6.54" (166 mm) H: 6.69"(170 mm) Weight: 28.5 lbs (12.95 kg) 3000 Watts </p>
		
<p>D5100/ 12V AGM 12 Volt High Performance AGM Power Cell MAX AMP : 3100 CA : 872A RC: 131min Ah: 66 L: 9.04" (230 mm) W: 5.43" (138 mm) H: 8.19"(208 mm) Weight: 43.2 lbs (19.6 kg) 3000 Watts </p>	<p>D4800/ 12V AGM 12 Volt High Performance AGM Power Cell MAX AMP : 3000 CA : 950A RC: 132min Ah: 74 L: 10.94" (299.72 mm) W: 6.93" (182.87 mm) H: 7.48"(172.72 mm) Weight: 48.2 lbs (21.87 kg) 3000 Watts </p>	<p>D3400/ 12V AGM 12 Volt High Performance AGM Power Cell MAX AMP : 3300 CA : 1150A RC: 160min Ah: 80 L: 10.24" (260 mm) W: 6.89" (175 mm) H: 7.16"(182 mm) Weight: 49.97 lbs (22.67 kg) 4000 Watts </p>

WARRANTY 3-YR

Thank you for purchasing this XS Power product!

We take great pride in our quality, value and performance and believe that this product will offer you trouble free operation throughout it's lifetime providing you take care to follow the simple instructions.

If you experience any problems with your product the warranty details are listed below.

LIMITED WARRANTY

- XS Power provides a three year warranty from the date of purchase, to the original purchaser. This warranty covers manufacturing defects in material and workmanship only.
- XS Power does not cover damage or failure caused by abuse, misuse, faulty installation, improper maintenance, or any repairs not carried out by XS Power.
- There will be no obligations or liability on the part of XS Power for consequential damages arising from the use of the product or any indirect damages with respect to loss of property, revenue, or costs for removal, installation, or re-installation.
- For warranty service, the product must be reported to XS Power to receive a unique RGA number (return goods authorization) and at that time you will be advised of where to send the faulty product.
- All shipping charges for returns should be prepaid. If the requested repairs or service are within the terms of

this warranty then the item will be returned to you on completion without any charge. The unit must be in its original packaging with any original accessories. XS Power will not be responsible or accept any liabilities for any loss or damage to addition items which are sent with returned product.

f) Provide a copy of receipt.

g) If the product is not covered under the terms of this warranty. XS Power will advise you of the costs to carry out any repairs necessary and the unit will be shipped to you on receipt of payment for the work including the return freight charges.

h) Under normal circumstance, we try to ensure we carry out warranty repairs within 5 working days; nevertheless, please allow 2 to 4 weeks for return of your product. We cannot be held responsible for delays in shipping.

Please take the time to complete your details below and return via Fax or Mail.

Title (ex. Mr/Miss)	First Name	M. Initial	Last Name								
_____	_____	_____	_____								
Address (house name/number & street)			Apt./Flat #								
_____			_____								
City	State	or Providence									
_____	_____	_____									
Country	Zip or Postal Code	Telephone # (inc. area code)									
_____	_____	_____									
E-mail	Battery Model #	Battery Serial #									
_____	_____	_____									
Date of Purchase	Place of Purchase										
_____	_____										
What brand charger do you use?		Model No.									
_____		_____									
<table border="1"><tr><td colspan="2">Where do you compete?</td></tr><tr><td>Sanctioning Body</td><td>Class</td></tr><tr><td>_____</td><td>_____</td></tr><tr><td>_____</td><td>_____</td></tr></table>				Where do you compete?		Sanctioning Body	Class	_____	_____	_____	_____
Where do you compete?											
Sanctioning Body	Class										
_____	_____										
_____	_____										



2847 John Deere Dr. Suite 102
Knoxville, TN 37917
Phone: 865-688-5953
Fax: 865-281-9844
www.4xspower.com
tech@xspowerbatteries.com
41-39-0014-3YR

Documents / Resources



[XS Power D950 XS Power Deep Cycle 12-Volt Battery](#) [pdf] Owner's Manual
D950 XS Power Deep Cycle 12-Volt Battery, D950 XS, Power Deep Cycle 12-Volt Battery, 12-Volt Battery

References

- [XS Power – Real Power, Unreal Performance](#)