



## Z-WAVE 79244 Plug in Smart Switch 1 Outlet Instruction Manual

[Home](#) » [Z-Wave](#) » Z-WAVE 79244 Plug in Smart Switch 1 Outlet Instruction Manual 

Z-WAVE 79244 Plug in Smart Switch 1 Outlet



## Contents

- 1 FCC
- 2 WARNING
- 3 Specifications
- 4 Introduction
- 5 Key Features
- 6 Product Overview
- 7 Button & Indicator Function Description
- 8 Adding Your Device To Hub
- 9 QR Code and DSK
- 10 Command Class
- 11 Basic Set Mapping
- 12 Indicator Command Class
- 13 Association Group
- 14 Configuration Parameters
- 15 Documents / Resources
  - 15.1 References
- 16 Related Posts

## FCC

Federal Communications Commission (FCC) Statement FCC Caution: Any changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate this equipment.

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

**NOTE:** This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures: Reorient or relocate the receiving antenna. Increase the separation between the equipment and receiver. Connect the equipment into an outlet on a circuit different from that to which the receiver is connected. Consult the dealer or an experienced radio/TV technician for help. This equipment should be installed and operated with minimum distance 20cm between the radiator and your body.

## WARNING

### RISK OF FIRE

RISK OF ELECTRICAL SHOCK

### RISK OF BURNS

### CONTROLLING APPLIANCES:

EXERCISE EXTREME CAUTION WHEN USING Z-Wave™ DEVICES TO CONTROL APPLIANCES. OPERATION OF THE Z-Wave™ DEVICE MAY BE IN A DIFFERENT ROOM THAN THE CONTROLLED APPLIANCE, ALSO AN UNINTENTIONAL ACTIVATION MAY OCCUR IF THE WRONG BUTTON ON THE REMOTE IS PRESSED. Z-Wave™ DEVICES MAY AUTOMATICALLY BE POWERED ON DUE TO TIMED EVENT PROGRAMMING. DEPENDING UPON THE APPLIANCE, THESE UNATTENDED OR UNINTENTIONAL OPERATIONS COULD POSSIBLY RESULT IN A HAZARDOUS CONDITION. FOR THESE REASONS, WE RECOMMEND DO NOT RETURN THIS PRODUCT TO THE STORE THE FOLLOWING: DO NOT USE Z-Wave™ DEVICES TO CONTROL ELECTRIC HEATERS OR ANY OTHER APPLIANCES WHICH MAY PRESENT A HAZARDOUS CONDITION DUE TO UNATTENDED OR UNINTENTIONAL OR AUTOMATIC POWER ON CONTROL.

## Specifications

ITEM	INFORMATION
Model	79244/ZWN4109
Power Supply	AC 120V 60HZ
Signal(Frequency)	908.42MHz
Long Range	Support
Range	Up to 100 feet line of sight between the Wireless Controller and the closest Z-Wave™ receiver module.
Operating Temperature Range	5-104° F (-10-40° C)

- Specifications subject to change without notice due to continuing product improvement
- Website:

## Introduction

This product can be operated in any Z-Wave network with other Z-Wave Plus™ certified devices from other manufacturers.

All non-battery operated nodes within the network will act as repeaters regardless of vendor to increase reliability of the network. Each module is designed to act as a repeater, which will re-transmit a radio frequency (RF) signal by routing the signal around obstacles and radio dead spots to ensure that the signal is received at its intended destination.

MP31Z is a security enabled Z-Wave Plus™ device. A security Enabled Z-Wave Plus™ Controller must be used in order to fully utilize the product.

### Type

GENERIC\_TYPE: GENERIC\_TYPE\_SWITCH\_BINARY(0x10)

SPECIFIC\_TYPE: SPECIFIC\_TYPE\_NOT\_USED(0x00)

APP ICON TYPE: ICON\_TYPE\_GENERIC\_ON\_OFF\_POWER\_SWITCH(0x0700)

## Key Features

- Remote ON/OFF control via the Z-Wave™ controller
- Manual ON/OFF control
- Support Association Group and Auto Report switch status
- Support firmware upgrades via Over-the-air (need Gateways support)
- Support Z-Wave™ Long Range (need Gateways support)
- Support Smart Start

## Product Overview

- A. on/off button
- B. LED
- C. Output Outlet
- E. Input



## Button & Indicator Function Description

### • Button Definition

1. Press 1x: Turn on/off Outlet Z-Wave network inclusion(ADD) /exclusion(REMOVE)
2. **Factory Reset:** Remove the switch from power. Press and hold the manual button, plug the switch in and continue holding the manual button for 3 seconds.  
**Note:** Please use this procedure only when the network primary controller is missing or otherwise inoperable.
3. Press 10x: Change the value of parameter 3.

## Adding Your Device To Hub

- The device support two methods of inclusion, When using a Z-Wave Plus™ certified controller choose Network Wide Inclusion or SmartStart.
  - TAP the button once times to ADD/INCLUDE the device.
- Network Wide Inclusion To A Z-Wave™ Network
  - TAP the button once times to REMOVE/EXCLUDE the device
  - Refer to your primary controller instructions to process the inclusion / exclusion setup procedure.
  - When prompted by your primary controller, click the Z-Wave button one times .
- The device is compatible with SmartStart.

SmartStart enabled products can be added into a Z-Wave™ network by scanning the Z-Wave QR Code found on the top of the outlet or the back of the box with a controller providing SmartStart inclusion. No further action is required and the SmartStart product will be added automatically within 10 minutes of being switched on and in the network vicinity.

### • Note:

Z-Wave Long Range device can only support be included via SmartStart. Extract the DSK from end device and paste it in to the Dsk Value in PC Controller, make sure the Long Range' option is ticked.

## QR Code and DSK

- The QR code are stocked to the side of the case, DSK is included in the QR code.
- The DSK code can be found on the DSK label which is attached on the packaging box.

PACKAGE	DEVICE
	

## Command Class

- Endpoint ROOT CC List

Command Class Name	Version	Required Security Class
Z-Wave Plus Info	V2	none
Security 2	V1	none
Supervision	V1	none
Transport Service	V2	none
Association	V2	highest granted
Association Group Information	V3	highest granted
Multi Channel Association	V3	highest granted
Version	V3	highest granted
Manufacturer Specific	V2	highest granted
Device Reset Locally	V1	highest granted
Power Level	V1	highest granted
Indicator	V3	highest granted
Firmware Update Meta Data	V5	highest granted
Configuration	V4	highest granted
Switch Binary	V2	highest granted
Basic	V2	highest granted

## Basic Set Mapping

- The Basic Set command is mapped to Binary Switch Set command.
- The Basic Report command is mapped to Binary Switch Report command

## Indicator Command Class

- The indicator (blue color) will flashes according the indicator set command received from HUB.

Indicator ID	Property ID
0x50 (NODE IDENTIFY)	0x03(ON OFF PERIOD)
0x50 (NODE IDENTIFY)	0x04(ON OFF CYCLES)
0x50 (NODE IDENTIFY)	0x05(ONE TIME ON OFF PERIOD)

## Association Group

- Endpoint ROOT

ID	Name	Node Count	Profile	Function
1	Lifeline	5	General: Lifeline	Device Reset Locally Notification Indicator Report Switch Binary Report
2	Basic Set	5	Control: Key01	Basic Set


## Configuration Parameters

Number	Name	Information	Format / Size	Read Only	Altering	Advanced	MIN	MAX	Default
03	Reaction of led	Change the reaction of the indicator.	1 byte unsigned integer	NO	NO	NO	0	3	1
41	Indicator brightness	Setting indicator's brightness.	1 bytes unsigned integer	NO	NO	NO	0	2	0
42	Restore status	Restore status after power failure.	1 bytes unsigned integer	NO	NO	NO	0	2	0
84	Reset factory	Set 1 to reset factory default	1 byte unsigned integer	NO	NO	NO	0	1	0



---

## Documents / Resources

	<a href="#">Z-WAVE 79244 Plug in Smart Switch 1 Outlet</a> [pdf] Instruction Manual 79244 Plug in Smart Switch 1 Outlet, 79244, Plug in Smart Switch 1 Outlet, Smart Switch 1 Outlet, Switch 1 Outlet
---	--

## References

- [User Manual](#)

[Manuals+](#), [Privacy Policy](#)

This website is an independent publication and is neither affiliated with nor endorsed by any of the trademark owners. The "Bluetooth®" word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. The "Wi-Fi®" word mark and logos are registered trademarks owned by the Wi-Fi Alliance. Any use of these marks on this website does not imply any affiliation with or endorsement.