

 **ZEBRA**
MC9300 Series Ultra
Rugged Mobile
Computer



ZEBRA MC9300 Series Ultra Rugged Mobile Computer User Guide

[Home](#) » [ZEBRA](#) » ZEBRA MC9300 Series Ultra Rugged Mobile Computer User Guide 

Contents

- [1 ZEBRA MC9300 Series Ultra Rugged Mobile Computer](#)
- [2 Product Usage Instructions](#)
- [3 MC9300 Configuration Guide](#)
- [4 Accessories](#)
- [5 Cradle options](#)
- [6 Chargers and batteries](#)
- [7 Spare Keypads](#)
- [8 FAQ](#)
- [9 Documents / Resources](#)
 - [9.1 References](#)
- [10 Related Posts](#)



ZEBRA MC9300 Series Ultra Rugged Mobile Computer



Product Usage Instructions

- The MC9300 offers various configuration options, including Wireless Option, RFID, Form Factor, Operating Temperature, Data Capture/Camera, Keyboard, Operating System, Memory Region, and Additional Features.
- CRD-MC93-2SUCHG-01 charges one device and one spare battery. Requires power supply PWR-BGA12V50W0WW and DC line cord CBL-DC-388A1-01.
- CRD-MC93-4SCHG-01 charges up to four devices. CRD-MC93-4SETH-01 provides Ethernet communication.
- USB communication with an additional USB-C cable. Requires power supply PWR-BGA12V50W0WW and country-specific AC line cord.
- Requires power supply PWR-BGA12V108W0WW and DC cord CBL-DC-381A1-01.

MC9300 Configuration Guide

CONFIGURATION OPTIONS:	MC9300	OPTION	DESCRIPTION
Wireless Option	MC930X-XXXXXXXX	0	WLAN 802.11 a/b/g/n/ac MU-MIMO & BT 5.0 BLE
RFID	MC93XB-XXXXXXXX	B	None
	MC93XP-XXXXXXXX	P	HF RFID Radio with NFC
	MC93XX-GXXXXXXXX	G	Gun
Form Factor	MC93XX-XSXXXXXXXX	S	Standard
Operating Temperature	MC93XX-XFXXXXXXXX	F	Freezer
Data Capture / Camera	MC93XX-XXAXXXXX	A	SE965 1D Laser
	MC93XX-XXBXXXXX	B	SE965 1D Laser + Front/Rear Camera
	MC93XX-XXCXXXXX	C	SE4750 2D Imager (EOL, replaced by SE4770)
	MC93XX-XXDXXXXX	D	SE4750 2D Imager + Front/Rear Camera (EOL, replaced by SE4770)
	MC93XX-XXHXXXXX	H	SE4770 2D Imager
	MC93XX-XXJXXXXX	J	SE4770 2D Imager + Front/Rear Camera
	MC93XX-XXEXXXXX	E	SE4850 2D imager
	MC93XX-XXFXXXXX	F	SE4850 2D imager + Front/Rear Camera
	MC93XX-XXGXXXXX	G	SE4750 DPM
	MC93XX-XXWXXXXX	W	SE4750 DPM Wide Angle
	MC93XX-XXXAXXXX	A	29 Key Function
Keyboard	MC93XX-XXXBXXXX	B	34 Key Function
	MC93XX-XXXCXXXX	C	43 Key Function
	MC93XX-XXXDXXXX	D	53 Key Standard Alpha Numeric
	MC93XX-XXXEXXXX	E	53 Key VT Alpha Numeric
	MC93XX-XXXFXXXX	F	53 Key 3270 Alpha Numeric
	MC93XX-XXXGXXXX	G	53 Key 5250 Alpha Numeric
	MC93XX-XXXHXXXX	H	58 Key Function Alpha Numeric
Operating System	MC93XX-XXXXAXXX	A	Android AOSP
	MC93XX-XXXXGXXX	G	Android GMS
Memory	MC93XX-XXXXX4XX	4	4 GB RAM / 32 GB Flash
Region	MC93XX-XXXXXXNA	NA	North America (USA, Canada, Puerto Rico)
	MC93XX-XXXXXXRW	RW	Rest of World (Excluding North America, China, and India)
	MC93XX-XXXXXXCN	CN	China
	MC93XX-XXXXXXIN	IN	India
Additional Features	MC93XX-XXXXXXXX-NI	NI	Non-Incendive (Class I, Div II)
	MC93XX-XXXXXXXX-TA	TA	TAA Compliant (Trade Agreement Act)
	MC93XX-XXXXXXXX-TI	TI	TAA Compliant (Trade Agreement Act), Non-Incendive (Class I, Div II)

MC9300 CONFIGURATIONS AVAILABLE



SKU Category	Features
--------------	----------

Base	<p>Platform</p> <p>Qualcomm Snapdragon 660 Octa-core, 2.2 GHz CPU, 4 GB RAM / 32 GB Flash</p> <p>802.11a/b/g/n/ac WiFi, 2 x 2 MU-MIMO, Bluetooth 4.0</p> <p>Sensors: Accelerometer, Gyroscope, Light Sensor</p> <p>Display</p> <p>4.3" WVGA (800×480) Color with Gorilla Glass touch panel</p>
Package 1	<p>Includes everything in a base unit as well as:</p> <p>NFC Radio Vibration Feedback</p>
Package 2	<p>Includes everything in a Package 1 unit as well as:</p> <p>Front and Rear color camera</p>
Freezer	<p>Includes everything in a Package 1 unit as well as:</p> <p>Sensor-driven Heated scan exit window, Freezer rated 5,000 mAh Lithium Ion Battery</p> <p>Condensation-Free operation -30°C/-22°F to 50°C/122°F</p> <p>Fog-Free display with optically bonded Gorilla Glass touch panel, Blue stripe around display, and Blue labelled battery</p>
DPM	<p>Includes everything in a Package 1 unit as well as:</p> <p>Standard or Wide Angle SE4750 DPM imager, Patented LED Light Diffusion Array</p>
Non-Incendive	<p>Available in a variety of SKU categories, as well as:</p> <p>UL Class I/II/III, Div 2 certification</p> <p>Orange stripe around display, Orange labelling on unit and battery</p>

Accessories

MC9300 Accessories Guide



Cradle options

Single slot cradle



Single Slot Cradle w/Spare Battery Charger:

- CRD-MC93-2SUCHG-01: Single slot USB cradle, with w/spare battery charger, charges one device and one spare battery. Allows USB communication to the device with an additional USB-C cable.
Requires: Power supply PWR-BGA12V50W0WW, DC line cord CBL-DC-388A1-01 and country-specific 3-wire AC line cord.

Main features

- USB communication
- Fast-charge while using MC93 PP+ batteries
- Charges one device and one spare battery
- Compatible with Level V and Level VI power supplies
- NOT COMPATIBLE WITH MC92

Additional accessories for a single-slot cradle

CBL-TC2X-USBC-01 or CBL-TC5X-USBC2A-01 USB-C cable for single slot cradle and cable cup

PWR-BGA12V50W0WW

- Level VI AC/DC power supply (brick, replacement for PWRS-14000-148R)
- AC Input: 100- 240V, 2.4A
- DC Output: 12V, 4.16A, 50W
- Requires: DC line cord and country-specific grounded AC line cord.



CBL-DC-388A1-01

- DC line cord for running the single slot cradles or battery chargers from a single Level VI power supply PWR-BGA12V50W0WW, Level VI replacement for PWRS-14000-148R.



23844-00-00R

- US AC line cord, 7.5 feet long, grounded, three wire for power supplies.



Multi-slot ShareCradles



Multi-Slot Cradle options:

- CRD-MC93-4SCHG-01: 4-slot charge-only cradle, charges up to four devices.
- CRD-MC93-4SETH-01: 4-slot Ethernet cradle, charges up to four devices, and provides Ethernet communication.
- All Cradles Require: Power supply PWR-BGA12V108W0WW, DC cord CBL-DC-381A1-01 and country specific 3 wire AC line cord.

Main features

- Charge only and Ethernet ShareCradle configurations
- Fast-charge while using MC93 PP+ batteries
- Charges 4 devices
- Compatible with Level V and Level VI power supplies
- Desk/Wall/Rack mount options
- NOT COMPATIBLE WITH MC92

Additional accessories for multi-slot cradles

PWR-BGA12V108W0WW

- Level VI AC/DC power supply (brick, Replacement for PWRS-14000-241R)
- AC Input: 100- 240V, 2.8A
- DC Output: 12V, 9A, 108W
- Requires: DC line cord and country-specific grounded AC line cord.



CBL-DC-381A1-01

- DC line cord for running multi-slot cradles from a single Level VI power supply PWR-BGA12V108W0WW, Level VI replacement for PWRS-14000-241R



23844-00-00R

- US AC line cord, 7.5 feet long, grounded, three-wire for power supplies.



BRKT-SCRD-SMRK-01

- Rack/Wall mounting bracket, allows to installation any multi-slot cradle on a wall or a 19" IT rack.



Chargers and batteries

Spare battery



BTRY-MC93-STN-01(Standard), BTRY-MC93-NI-01 (Non Incendive)

- PowerPrecision+ Lithium Ion 7000 mAh battery provides advanced State of Charge and State of Health, supports fast-charge while using MC93 cradles and chargers.
- Pack of 10 batteries: BTRY-MC93-STN-10, BTRY-MC93-NI-10

BTRY-MC93-FZ-01 (Freezer)

- PowerPrecision+ Lithium Ion 5000 mAh Freezer rated (-30C) battery, provides advanced State of Charge and State of Health, supports fast-charge while using MC93 cradles and chargers.
- Pack of 10 batteries: BTRY-MC93-FZ-10

Spare battery charger options:



Main features

- 4-slot and 16-slot configurations
- Fast-charge while using MC93 PP+ batteries
- Compatible with Level V and Level VI power supplies
- Desk/Wall/Rack mount options
- NOT COMPATIBLE WITH MC92 BATTERIES

SAC-MC93-4SCHG-01:

- 4-slot battery charger, charges four spare batteries. Requires: Power supply PWR-BGA12V50W0WW, DC line cord CBL-DC-388A1-01 and, country country-specific 3-wire AC line cord.

SAC-MC93-16SCHG-01:

- 16-slot battery charger, charges sixteen spare batteries. Requires: Power supply PWR-BGA12V108W0WW, DC cord CBL-DC-381A1-01, country country-specific 3-wire AC line cord.

Accessories for battery chargers:

PWR-BGA12V50W0WW

- Level VI AC/DC power supply. AC Input: 100- 240V, 2.4A, DC Output: 12V, 4.16A, 50W Requires: DC line cord and country-specific grounded AC line cord.



CBL-DC-388A1-01

- DC line cord for running the single-slot cradles or battery chargers from a single Level VI power supply, PWR-BGA12V50W0WW.



PWR-BGA12V108W0WW

- Level VI AC/DC Power Supply. AC Input: 100- 240V, 2.8A, DC Output: 12V, 9A, 108W Requires: DC line cord and country-specific grounded AC line cord.



CBL-DC-381A1-01

- DC line cord for running multi-slot cradles from a single Level VI power supply, PWR-BGA12V108W0WW.



23844-00-00R

- US AC line cord, 7.5 feet long, grounded, three-wire for power supplies.



BRKT-SCRD-SMRK-01

- Rack/Wall mounting bracket allows to the installation of the 16-slot battery charger or up to four 4-slot battery chargers on a wall or a 19" IT rack.



Spare Keypads

Field replaceable spare keypads



53 Key Standard

KYPD-MC9353ANR-01
KYPD-MC9353ANR-10



53 Key TE 5250

KYPD-MC93535250-01
KYPD-MC93535250-10



53 Key TE 3270

KYPD-MC93533270-01
KYPD-MC93533270-10



53 Key TE VT

KYPD-MC9353VT-01
KYPD-MC9353VT-10



43 Key Function

KYPD-MC9343FN-01
KYPD-MC9343FN-10



34 Key Function

KYPD-MC9334FNR-01
KYPD-MC9334FNR-10



58 Key Func AN

KYPD-MC9358ANR-01
KYPD-MC9358ANR-10



29 Key Function

KYPD-MC9329NMR-01
KYPD-MC9329NMR-10

Other charge accessories

Backwards compatibility



ADP-MC93-CRDCUP-01

Charge only adapter for backwards compatibility with MC9x cradles, the adapter can be installed on any MC9x single slot or multi-slot cradle (charge only or Ethernet) allowing to charge a MC93 device (the adapter does not provide USB or Ethernet communication and does not provide fast-charge).

USB charge cable

CBL-MC93-USBCHG-01: USB cable, provides fast-charge when an MC93 PP+ battery and a wall adapter is used, it also allows USB communication to the device when connected to a PC. Requires: CBL-TC2X-USBC-01 and Power supply PWR-WUA5V12W0US



Additional accessories for the USB cable

PWR-WUA5V12W0US

Level VI power supply (wall adapter) 100-240 VAC, 5V, 2.5A with US plug.
Other countries:

- Australia: PWR-WUA5V12W0AU
- Brazil: PWR-WUA5V12W0BR
- China: PWR-WUA5V12W0CN
- Europe: PWR-WUA5V12W0EU
- India: PWR-WUA5V12W0IN
- Korea: PWR-WUA5V12W0KR
- UK: PWR-WUA5V12W0GB

Soft goods for gun configurations

Holster

SG-MC9X-SHLSTG-01

- Fabric holster secures to a belt or a shoulder strap. Allows carrying the gun device on the hip or cross-body. Requires a belt or shoulder strap ordered separately.



Shoulder strap 58-40000-007R

- Universal shoulder strap for fabric holster.

Belt for holster 11-08062-02R

- Universal belt for fabric holster.



Protective boot

SG-MC93-RBTG-01

Protective boot for gun configurations protects the device from wear and tear.



Hand strap

SG-MC93-HDSTPG-01

Spare hand strap for gun configurations (pkg 1)



Other accessories



MNT-MC93-FLCHKT-01

Unpowered forklift mount. Allows installing the device on a roll bar or square surface of a forklift. Includes: Forklift holder (MNT-MC93-FLCH-01), RAM double socket arm for 1" ball (MNT-RAM-B201U) , RAM forklift clamp 2.5" max width square rail base with 1" ball (MNT-RAM-B247U25).

BRKT-SCRD-SMRK-01

Rack/Wall mounting bracket, allows to install any Multi-slot ShareCradle, the 16-slot battery charger or up to four 4-slot battery chargers on a wall or a 19" server rack.



Other accessories



MISC-MC93-SCRN-01

Tempered glass screen protector
(Qty. 5)



SG-TC7X-STYLUS-03

Stylus with coiled tether (Qty. 3).
Made of conductive carbon-filled plastic material, optimized for enterprise durability.



HS3100-OTH

HS3100 Rugged Bluetooth headset with over-the-head headband.
Included HS3100 boom module and HSX100 OTH headband module.

HS3100-BTN-L

HS3100 Rugged Bluetooth headset with behind-the-neck headband (left).
Included HS3100 boom module and HSX100 BTN-L headband module.

Other accessories

Country-specific AC grounded line cords

Country specific AC grounded line cords

Part Number	Description
23844-00-00R	AC line cord, 7.5 feet long, grounded, three wire. Associated Country: US
50-16000-217R	AC Line Cord, 1.9M, grounded, three wire, AS 3112 plug. Associated Country: Australia, New Guinea
50-16000-218R	AC Line Cord, 1.8M, grounded, three wire, NEMA 1-15P plug. Associated Country: Japan
50-16000-219R	AC Line Cord, 1.8M, three wire, grounded BS1363 plug. Associated Countries: Hong Kong, Iraq, Malaysia, Singapore, United Kingdom
50-16000-220R	AC Line Cord, 1.8M, grounded, three wire CEE 7/7 plug. Associated Countries: Europe, Abu Dhabi, Bolivia, Dubai, Egypt, Iran, Korea, Russia, Vietnam
50-16000-256R	AC Line Cord, 1.8M, grounded, three wire, CEE7/7 plug. Associated Country: Korea
50-16000-257R	AC Line Cord, 1.8M, grounded, three wire, IEC 60320 C13 plug. Associated Country: China
50-16000-669R	AC Line Cord, 1.9 M grounded, three wire, BS 546 Plug. Associated Country: India
50-16000-671R	AC Line Cord, 1.8M grounded, CIE 23-16 plug. Associated Country: Italy
50-16000-672R	AC Line Cord, 1.9M grounded, three wire, S132 Plug. Associated Country: Israel
50-16000-727R	AC Line Cord, 1.9M grounded, three wire. Associated Country: Brazil


Country specific wall adapters

Part Number	Description
PWR-WUA5V12W0AU	Level VI power supply (wall adapter) 100-240 VAC, 5V, 2.5A with Australia plug
PWR-WUA5V12W0BR	Level VI power supply (wall adapter) 100-240 VAC, 5V, 2.5 A with Brazil plug
PWR-WUA5V12W0CN	Level VI power supply (wall adapter) 100-240 VAC, 5V, 2.5A with China plug
PWR-WUA5V12W0EU	Level VI power supply (wall adapter) 100-240 VAC, 5V, 2.5A with Europe plug
PWR-WUA5V12W0GB	Level VI power supply (wall adapter) 100-240 VAC, 5V, 2.5A with UK plug
PWR-WUA5V12W0IN	Level VI power supply (wall adapter) 100-240 VAC, 5V, 2.5A with India plug
PWR-WUA5V12W0KR	Level VI power supply (wall adapter) 100-240 VAC, 5V, 2.5A with Korea plug
PWR-WUA5V12W0US	Level VI power supply (wall adapter) 100-240 VAC, 5V, 2.5A with US plug

FAQ

- **Q:** What are the different configurations available for the MC9300?
- **A:** The MC9300 is available in various configurations, including base package, Package 1, Package 2, Freezer, and DPM Non-Incendive with different features and accessories.
- **Q:** How many devices can the Multi-Slot Cradle charge?
- **A:** The CRD-MC93-4SCHG-01 Multi-Slot Cradle can charge up to four devices simultaneously.

Documents / Resources

	ZEBRA MC9300 Series Ultra Rugged Mobile Computer [pdf] User Guide C930X-XXXXXXX, MC93XB-XXXXXXX, MC93XP-XXXXXXX, MC9300 Series Ultra Rugged Mobile Computer, MC9300 Series, Ultra Rugged Mobile Computer, Rugged Mobile Computer, Mobile Computer
---	--

References

- [User Manual](#)

[Manuals+](#), [Privacy Policy](#)

This website is an independent publication and is neither affiliated with nor endorsed by any of the trademark owners. The "Bluetooth®" word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. The "Wi-Fi®" word mark and logos are registered trademarks owned by the Wi-Fi Alliance. Any use of these marks on this website does not imply any affiliation with or endorsement.